

# NEWTON

## **Penetrating protection & antifouling-agent for building stone (Finish in rich color)**

### **Features**

---

Once applied on the surface of stone, NEWTON penetrates into material deeply forming an outstanding weather-resistant and waterproof layer by chemical reaction.

Deepens the color.

Excellent oil-repellency prevents stains and soiling from gathering on the surface, and daily maintenance only requires washing off with water.

Prevents water absorption by lowering the absorption rate, and prevent cracking from freezing.

Fine weather ability enables prevention from weathering, deteriorating, and efflorescence of stone.



### **Applications**

---

Protection and Prevention of granite, marble, terrazzo, tile and cement from stains and dirt.

### **Properties**

---

Solvent-based coating solution

Fire Service Act:Category IV, Class I petroleums, dangerous grade 2

FLAMMABLE

### **Coverage**

---

No. of Coats:1 Coat

Polished Marble & Granite 40~50 m<sup>2</sup>/l

Burner finished Granite 15~20 m<sup>2</sup>/l

Glazed Tile 30~40 m<sup>2</sup>/l

Unglazed Tile & Bricks 15~20 m<sup>2</sup>/l

Faux Stone, Mortar & Joint Cement 5~10 m<sup>2</sup>/l

### **Available Sizes**

---

4 Liter & 16 Liter

